
JIANGSU CHANGJING ELECTRONICS TECHNOLOGY CO., LTD.

TO-92 Plastic-Encapsulate Transistors


MPS2907A TRANSISTOR (PNP)



FEATURES


- Complementary NPN Type available (MPS2222A)

MARKING



MPS2907A=Device code
Z=Rank of h_{FE}
XXX=Code
GXX=Green molding compound device
CXX=Normal molding compound device

Equivalent Circuit



ORDERING INFORMATION

Part Number	Package	Packing Method	Pack Quantity
MPS2907A	TO-92	Bulk	1000pcs/Bag
MPS2907A-TA	TO-92	Tape	2000pcs/Box

MAXIMUM RATINGS (T_a=25℃ unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	-60	V
V_{CEO}	Collector-Emitter Voltage	-60	V
V_{EBO}	Emitter-Base Voltage	-5	V
I_C	Collector Current -Continuous	-600	mA
P_D	Collector Power Dissipation	625	mW
$R_{\theta JA}$	Thermal Resistance from Junction to Ambient	200	℃/W
T_J,T_{stg}	Operation Junction and Storage Temperature Range	-55~+150	℃

ELECTRICAL CHARACTERISTICS


T_a=25℃ unless otherwise specified


Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	I_C=-10μA,I_E=0	-60			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	I_C=-10mA,I_B=0	-60			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	I_E=-10μA,I_C=0	-5			V
Collector cut-off current	I_{CBO}	V_{CB}=-50V,I_E=0			-10	n A
Collector cut-off current	I_{CEX}	V_{CE}=-30V,$V_{EB(off)}$=-0.5V			-50	nA
Emitter cut-off current	I_{EBO}	V_{EB}=-3V,I_C=0			-10	nA
DC current gain	$h_{FE(1)}$	V_{CE}=-10V,I_C=-0.1mA	78			
	$h_{FE(2)}$	V_{CE}=-10V,I_C=-150mA	100		300	
	$h_{FE(3)}$	V_{CE}=-10V,I_C=-500mA	52			
Collector-emitter saturation voltage	$V_{CE(sat)}$	I_C=-150mA,I_B=-15mA			-0.4	V
	$V_{CE(sat)}$	I_C=-500mA,I_B=-50mA			-0.67	V
Base-emitter saturation voltage	$V_{BE(sat)}$	I_C=-150mA,I_B=-15mA			-1	V
	$V_{BE(sat)}$	I_C=-500mA,I_B=-50mA			-1.2	V
Transition frequency	f_T	V_{CE}=-20V,I_C=-50mA,f=100MHz	200			MHz
Delay time	t_d	V_{CC}=-30V,Ic=-150mA,			10	ns
Rise time	t_r	I_{B1}=-I_{B2}=-15mA			25	ns
Storage time	t_S	V_{CC}=-6V,Ic=-150mA,			225	ns
Fall time	t_f	I_{B1}=-I_{B2}=-15mA			60	ns


CLASSIFICATION OF $h_{FE(2)}$


Rank	L	H
Range	100-200	200-300


Typical Characteristics






















TO-92 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	3.300	3.700	0.130	0.146
A1	1.100	1.400	0.043	0.055
b	0.380	0.550	0.015	0.022
c	0.360	0.510	0.014	0.020
D	4.300	4.700	0.169	0.185
D1	3.430		0.135	
E	4.300	4.700	0.169	0.185
e	1.270 TYP		0.050 TYP	
e1	2.440	2.640	0.096	0.104
L	14.100	14.500	0.555	0.571
Φ		1.600		0.063
h	0.000	0.380	0.000	0.015


TO-92 Suggested Pad Layout




Note:
1.Controlling dimension:in millimeters.
2.General tolerance:± 0.05mm.
3.The pad layout is for reference purposes only.

NOTICE
JSCJ reserves the right to make modifications,enhancements,improvements,corrections or other changes without further notice to any product herein. JSCJ does not assume any liability arising out of the application or use of any product described herein.

TO-92 Tape and Reel



Dimiensions are in millimeter								
A1	A	T	P	P0	P2	F1	F2	W
4.5	4.5	3.5	12.7	12.7	6.35	2.5	2.5	18.0
W0	W1	W2	H	H0	D0	t1	t2	ΔP
6.0	9.0	1.0 MAX.	19.0	16.0	4.0	0.4	0.2	0



Package	Box	Box Size(mm)	Carton	Carton Size(mm)
TO-92	2000 pcs	333×162×43	20,000 pcs	350×340×250