SZCJ Shenzhen Changji Semiconductor Co., LTD.

SMCG Plastic-Encapsulate Diodes

MURS460 Super Fast Recovery Rectifier Diodes

Features

- $I_{F(AV)}$ 4A
- V_{RRM} 600V
- High surge current capability
- Polarity: Color band denotes cathode


Applications

- Rectifier

Marking

- MURS460

SMCG



Limiting Values (Absolute Maximum Rating)

Item	Symbol	Unit	Test Conditions	MURS460
Repetitive Peak Reverse Voltage	V_{RRM}	V		600
Maximum RMS Voltage	V_{RMS}	V		420
Maximum DC Blocking Voltage	V_{DC}	V		600
Average Forward Current	$I_{F(AV)}$	A	60Hz Half-sine wave, Resistance load, T_L=75℃	4.0
Surge(Non-repetitive)Forward Current	I_{FSM}	A	60Hz Half-sine wave, 1 cycle, Ta=25℃	110
Operation Junction and Storage Temperature Range	T_J,T_{STG}	℃		-55 ~ +150

Electrical Characteristics (T=25 ℃Unless otherwise specified)

Item	Symbol	Unit	Test Condition		MURS460
Maximum Peak Forward Voltage	V_F	V	I_F=4.0A		1.28
Maximum Reverse recovery time	t_{rr}	ns	I_F=0.5A,I_R=1.0A Irr=0.25A		50
Maximum Peak Reverse Current	I_{RRM1}	μA	V_{RM}=V_{RRM}	Ta =25 ℃	10
	I_{RRM2}			Ta =150 ℃	250
Typical Junction Capacitance	C_J	pF	Measured at 1MHz and applied reverse voltage of 4.0V D.C.		40
Thermal Resistance(Typical)	$R_{\theta J-A}$	℃/W	Between junction and ambient		40[1)]

Notes:

Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.2" x 0.2" (5.0 mm x 5.0 mm) copper pad areas

Typical Characteristics

FIG.1: FORWARD CURRENT DERATING CURVE




FIG.2: MAXIMUM NON-REPETITIVE FORWARD URGE CURRENT




FIG.3: TYPICAL FORWARD CHARACTERISTICS




FIG.4：TYPICAL REVERSE CHARACTERISTICS






FIG.5: Diagram of circuit and Testing wave form of reverse recovery time




SMCG Package Outline Dimensions



Dimensions in inches and (millimeters)

SMCG Suggested Pad Layout



Note:
1.Controlling dimension:in millimeters.
2.General tolerance:± 0.05mm.
3.The pad layout is for reference purposes only.

NOTICE

SZCJ reserves the right to make modifications,enhanc nts,improvements,corrections or other es without further notice to any product herein.SZCJ does not assume any liability arising out of the application or use of any product described .

Reel Taping Specifications For Surface Mount Devices- SMCG




FIG:CONFIGURATION OF SURFACE MOUNTED DEVICES TAPING

ITEM	SYMBOL	SMCG mm(inch)
Carrier width	A	6.05±0.1(0.238±0.004)
Carrier length	B	8.31±0.1(0.327±0.004)
Carrier depth	C	2.70±0.1(0.106±0.004)
Sprocket hole	d	1.55±0.05(0.061±0.002)
Reel outside diameter	D	330±2.0(13±0.079)
Reel inner diameter	D1	75±1.0(2.95±0.039)
Feed hole diameter	D2	13±0.5(0.512±0.020)
Strocket hole position	E	1.75±0.1(0.069±0.004)
Punch hole position	F	7.65±0.05(0.301±0.002)
Punch hole pitch	P	8.0±0.1(0.315±0.004)
Sprocket hole pitch	P0	4.0±0.1(0.157±0.004)
Embossment center	P1	2.0±0.1(0.079±0.004)
Totall tape thickness	T	0.3±0.1(0.012±0.004)
Tape width	W	16.0±0.2(0.630±0.008)
Reel width	W1	24.0±2.0(0.945±0.079)

NOTE:Devices are packed in accordance with EIA standard RS-481-A and specification given above.