
JIANGSU CHANGJING ELECTRONICS TECHNOLOGY CO., LTD.

SOT-89-3L Plastic-Encapsulate Transistors

PXT8550 TRANSISTOR (PNP)

SOT-89-3L




1. BASE
2. COLLECTOR
3. EMITTER

FEATURES

Compliment to PXT8050

MARKING: Y2



Solid dot = Green molding compound device.

MAXIMUM RATINGS (Ta=25℃ unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	-40	V
V_{CEO}	Collector-Emitter Voltage	-25	V
V_{EBO}	Emitter-Base Voltage	-5	V
I_C	Collector Current -Continuous	-1.5	A
P_C	Collector Power Dissipation	0.5	W
$R_{\Theta JA}$	Thermal Resistance From Junction To Ambient	250	℃/W
T_J,T_{stg}	Operation Junction and Storage Temperature Range	-55~150	℃

ELECTRICAL CHARACTERISTICS (T_a=25℃ unless otherwise specified)


Parameter	Symbol	Test conditions	Min	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	I_C= -100μA, I_E=0	-40		V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	I_C= -0.1mA, I_B=0	-25		V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	I_E= -100μA, I_C=0	-5		V
Collector cut-off current	I_{CBO}	V_{CB}= -40 V,I_E=0		-0.1	μA
Collector cut-off current	I_{CEO}	V_{CE}= -20V, I_B=0		-0.1	μA
Emitter cut-off current	I_{EBO}	V_{EB}= -5V, I_C=0		-0.1	μA
DC current gain	$h_{FE(1)}$	V_{CE}= -1V, I_C= -100mA	85	400	
	$h_{FE(2)}$	V_{CE}= -1V, I_C= -800mA	40		
Collector-emitter saturation voltage	$V_{CE(sat)}$	I_C=-800mA, I_B= -80mA		-0.5	V
Base-emitter saturation voltage	$V_{BE(sat)}$	I_C=-800mA, I_B= -80mA		-1.2	V
Base-emitter on voltage	$V_{BE(on)}$	Ic=-1V,V_{CE}=-10mA		-1	V
Base-emitter positive favor voltage	V_{BEF}	I_B=-1A		-1.55	V
Transition frequency	f_T	V_{CE}= -10V, I_C= -50mA	100		MHz
output capacitance	C_{ob}	V_{CB}=-10V,I_E=0,f=1MHz		20	pF

CLASSIFICATION OF $h_{FE(1)}$


Rank	B	C	D	D3
Range	85-160	120-200	160-300	300-400

Typical Characteristics


Static Characteristic




h_{FE} —— I_C




V_{BEsat} —— I_C




V_{CEsat} —— I_C




V_{BE} —— I_C




C_{ob}/ C_{ib} —— V_{CB}/ V_{EB}




f_T —— I_C



P_C —— T_a




SOT-89-3L Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.400	1.600	0.055	0.063
b	0.320	0.520	0.013	0.020
b1	0.400	0.580	0.016	0.023
c	0.350	0.440	0.014	0.017
D	4.400	4.600	0.173	0.181
D1	1.550 REF.		0.061 REF.	
E	2.300	2.600	0.091	0.102
E1	3.940	4.250	0.155	0.167
e	1.500 TYP.		0.060 TYP.	
e1	3.000 TYP.		0.118 TYP.	
L	0.900	1.200	0.035	0.047

SOT-89-3L Suggested Pad Layout




Note:
1.Controlling dimension:in millimeters.
2.General tolerance:±0.05mm.
3.The pad layout is for reference purposes only.

NOTICE
JSCJ reserves the right to make modifications,enhancements,improvements,corrections or other changes without further notice to any product herein. JSCJ does not assume any liability arising out of the application or use of any product described herein.

SOT-89-3L Tape and Reel

SOT-89-3L Embossed Carrier Tape




Packaging Description:


SOT-89-3L parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 1,000 units per 7" or 18.0 cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-89-3L	4.85	4.45	1.85	Ø1.50	1.75	5.50	4.00	8.00	2.00	12.00

SOT-89-3L Tape Leader and Trailer



SOT-89-3L Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø180.00	60.00	R32.00	R86.50	R30.00	Ø13.00	13.20	16.50

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
1000 pcs	7 inch	10,000 pcs	203×203×195	40,000 pcs	438×438×220	