
SZCJ Shenzhen Changji Semiconductor Co., LTD.

# GBP Plastic-Encapsulate Bridge Rectifier

## GBP4005 THRU GBP410 General Purpose Bridge Rectifier

### Features

- $I_O$ 4A
- VRRM 50V-1000V
- High surge current capability
- Glass passivated chip




### Applications

- General purpose 1 phase Bridge rectifier applications

### Marking

- GBP4XX

XX：From 005 To 10

### Limiting Values (Absolute Maximum Rating)

| Item | Symbol | Unit | Conditions | GBP4 | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | | 005 | 01 | 02 | 04 | 06 | 08 | 10 |
| Repetitive Peak Reverse Voltage | $V_{RRM}$ | V | | 50 | 100 | 200 | 400 | 600 | 800 | 1000 |
| Average Rectified Output Current | $I_O$ | A | 60Hz sine wave, R-load ,Ta=50℃ | 4.0 | | | | | | |
| Surge(Non-repetitive)Forward Current | $I_{FSM}$ | A | 60$H_Z$ half-sine wave, 1 cycle, $T_j$=25℃ | 125 | | | | | | |
| Current Squared Time | $I^2t$ | $A^2S$ | 1ms≤t<8.3ms Tj=25℃， Rating of per diode | 64.8 | | | | | | |
| Storage Temperature | $T_{stg}$ | ℃ | | -55 ~+150 | | | | | | |
| Junction Temperature | $T_j$ | ℃ | | -55 ~+150 | | | | | | |

### Electrical Characteristics（$T_a$=25℃ Unless otherwise specified）

| Item | Symbol | Unit | Test Condition | Max |
|---|---|---|---|---|
| Peak Forward Voltage | $V_{FM}$ | V | $I_{FM}$=4.0A, Pulse measurement, Rating of per diode | 1.1 |
| Peak Reverse Current | $I_{RRM}$ | μA | $V_{RM}$=$V_{RRM}$ , Pulse measurement, Rating of per diode | 10 |
| Thermal Resistance | $R_{\theta J-A}$ | ℃/W | Between junction and ambient | 47 |
| | $R_{\theta J-C}$ | | Between junction and case | 10 |

## Typical Characteristics

FIG.1-MAXIMUM NON-REPETITIVE SURGE CURRENT





FIG.2-FORWARD DERATING CURRENT





FIG.3-TYPICAL FORWARD CHARACTERISTICS








FIG.4-TYPICAL REVERSE CHARACTERISTICS



## GBP Package Outline Dimensions




Dimensions in inches and (milimeters)

NOTICE

SZCJ reserves the right to make modifications,enhancements,improvements,corrections or other changes without further notice to any product herein. SZCJ does not assume any liability arising out of the application or use of any product described .