
JIANGSU CHANGJING ELECTRONICS TECHNOLOGY CO., LTD.

SOT-89-3L Plastic-Encapsulate Transistors

SOT-89-3L



1. BASE
2. COLLECTOR
3. EMITTER

BCX54,BCX55,BCX56 TRANSISTOR (NPN)


FEATURES

- PNP Complements to BCX51,BCX52,BCX53
- Low Voltage
- High Current


APPLICATIONS

- Driver Stages of Audio Amplifiers


MARKING:



BCX54 BCX54-10 BCX54-16



BCX55 BCX55-10 BCX55-16



BCX56 BCX56-10 BCX56-16

Solid dot = Green molding compound device.

MAXIMUM RATINGS (T_a=25℃ unless otherwise noted)

Symbol	Parameter		Value	Unit
V_{CBO}	Collector-Base Voltage	BCX54	45	V
		BCX55	60	
		BCX56	100	
V_{CEO}	Collector-Emitter Voltage	BCX54	45	V
		BCX55	60	
		BCX56	80	
V_{EBO}	Emitter-Base Voltage		5	V
I_C	Collector Current		1	A
I_B	Base Current		0.1	A
I_{BM}	Peak base Current (tp<1ms)		0.2	A
P_C	Collector Power Dissipation		500	mW
$R_{\theta JA}$	Thermal Resistance From Junction To Ambient		250	℃/W
T_J,T_{stg}	Operation Junction and Storage Temperature Range		-55~+150	℃
T_{opr}	Operation Temperature Range		-25~+125	℃


Parameter	Symbol	Test conditions		Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	I_C=100μA,I_E=0	BCX54	45			V
			BCX55	60			
			BCX56	100			
Collector-emitter breakdown voltage	$V_{(BR)CEO*}$	I_C=10mA,I_B=0	BCX54	45			V
			BCX55	60			
			BCX56	80			
Emitter-base breakdown voltage	$V_{(BR)EBO}$	I_E=10μA,I_C=0		5			V
Collector cut-off current	I_{CBO}	V_{CB}=30V,I_E=0				0.1	μA
Emitter cut-off current	I_{EBO}	V_{EB}=5V,I_C=0				0.1	μA
DC current gain	$h_{FE(1)*}$	V_{CE}=2V, I_C=5mA		40			
	$h_{FE(2)*}$	V_{CE}=2V, I_C=150mA		63		250	
	$h_{FE(3)*}$	V_{CE}=2V, I_C=0.5A		25			
Collector-emitter saturation voltage	$V_{CE(sat)*}$	I_C=0.5A,I_B=50mA				0.5	V
Base -emitter voltage	V_{BE*}	V_{CE}=2V, I_C=0.5A				1	V
Transition frequency	f_T	V_{CE}=5V,I_C=10mA, f=100MHz			130		MHz


***** Pulse Test


CLASSIFICATION OF $h_{FE(2)}$


RANK	**BCX54** **BCX55** **BCX56**	**BCX54-10** **BCX55-10** **BCX56-10**	**BCX54-16** **BCX55-16** **BCX56-16**
RANGE	63 – 250	63 – 160	100 – 250


Typical Characteristics






















SOT-89-3L Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.400	1.600	0.055	0.063
b	0.320	0.520	0.013	0.020
b1	0.400	0.580	0.016	0.023
c	0.350	0.440	0.014	0.017
D	4.400	4.600	0.173	0.181
D1	1.550 REF.		0.061 REF.	
E	2.300	2.600	0.091	0.102
E1	3.940	4.250	0.155	0.167
e	1.500 TYP.		0.060 TYP.	
e1	3.000 TYP.		0.118 TYP.	
L	0.900	1.200	0.035	0.047

SOT-89-3L Suggested Pad Layout




Note:
1.Controlling dimension:in millimeters.
2.General tolerance:±0.05mm.
3.The pad layout is for reference purposes only.

NOTICE
JSCJ reserves the right to make modifications,enhancements,improvements,corrections or other changes without further notice to any product herein. JSCJ does not assume any liability arising out of the application or use of any product described herein.

SOT-89-3L Tape and Reel

SOT-89-3L Embossed Carrier Tape




Packaging Description:


SOT-89-3L parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 1,000 units per 7" or 18.0 cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-89-3L	4.85	4.45	1.85	Ø1.50	1.75	5.50	4.00	8.00	2.00	12.00

SOT-89-3L Tape Leader and Trailer



SOT-89-3L Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø180.00	60.00	R32.00	R86.50	R30.00	Ø13.00	13.20	16.50

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
1000 pcs	7 inch	10,000 pcs	203×203×195	40,000 pcs	438×438×220	