szcjsemi.com

SZCJ

Ultra-Small High-Precision Voltage Detector

CJ808 Series

■ INTRODUCTION

The Series is a series of high-precision voltage detectors with a built-in delay time generator of fixed time deve-loped using CMOS process.

The detection voltage is fixed internally, with an accuracy of ±2.0%.

■ APPLICATIONS

- Memory battery back-up circuits
- Power-on reset circuits
- Power failure detection
- Power monitor for portable equipment such as notebook computers, digital cameras, PDA, and cellular phones.
- Constant voltage power monitors for cameras,video equipment and com-munication devices.
- Power monitor for microcomputers and reset for CPUs.

■ FEATURES

- Ultra-low current consumption: 0.9μA@3.5V(Typ.)
- High-precision detection voltage: ±2.0%
- Hysteresis characteristics: -VDET×5%(Typ.)
- Operating voltage range: 0.95V to 7.0V
- Detection voltage: 1.5V to 6.0V (10mV step)
- ESD(HMB): ±8K
- Output forms:
  NMOS open-drain output (Active Low)
  CMOS output (Active Low)


■ ORDER INFORMATION

CJ808①②③④⑤


DESIGNATOR	SYMBOL	DESCRIPTION
①	C	CMOS
	N	NMOS open drain
②③④	Integer	DetectionVoltage (1.50V~6.00V), "④"elide when it is "0" e.g. 3.0V=②:3, ③:0 2.93V=②:2, ③:9, ④:3
⑤	M	Package：SOT-23-3L
	MR	Package：SOT-23-5L
	P	Package：SOT-89-3L
	N	Package：SOT-23

■ BLOCK DIAGRAMS

NMOS open-drain




CMOS output




■ PIN CONFIGURATION

SOT-23
SOT-23-3L




PIN NO.	N/M	FUNCTION
1	V_{OUT}	Voltage detection output pin
2	V_{SS}	Ground
3	V_{DD}	Voltage input pin

SOT-89-3L



PIN NO.	P	FUNCTION
1	V_{OUT}	Voltage detection output pin
2	V_{DD}	Voltage input pin
3	V_{SS}	Ground

SOT-23-5L



PIN NO.	MR	FUNCTION
1	V_{OUT}	Voltage detection output pin
2	V_{DD}	Voltage input pin
3	V_{SS}	Ground
4	NC	No connection
5	NC	No connection

■ ABSOLUTE MAXIMUM RATINGS

(Ta=25°C, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNITS
Power supply voltage		V_{DD}	$V_{SS}-0.3 \sim V_{SS}+8$	V
Output voltage		V_{OUT}	$V_{SS}-0.3 \sim V_{SS}+8$	V
Power dissipation	SOT-23	PD	250	mW
	SOT-23-3L		400	mW
	SOT-89-3L		500	mW
	SOT-23-5L		500	mW
Operating ambient temperature		T_{opr}	−40 ~+85	°C
Storage temperature		T_{stg}	−40 ~+125	°C
Soldering Temperature & Time		T_{solder}	260℃, 10s	

■ ELECTRICAL CHARACTERISTICS


(Ta=25°C, unless otherwise specified)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
Detection voltage***1**	$-V_{DET}$	—		$-V_{DET(S)}$ ×0.98	$-V_{DET(S)}$	$-V_{DET(S)}$ ×1.02	V
Hysteresis width	V_{HYS}	—		0.02× $-V_{DET(S)}$	0.05× $-V_{DET(S)}$	0.08× $-V_{DET(S)}$	V
Current consumption	I_{SS}	$V_{DD}=-V_{DET}+0.5V$	CJ808 C/N 20～26	—	1.0	2.0	uA
			CJ808 C/N 26～39	—	1.2	2.5	uA
			CJ808 C/N 39～60	—	1.5	3.0	uA
Operating voltage	V_{DD}	—		0.95	—	7	V
Output current	I_{OUT}	NMOS: V_{OUT} =0.5 V V_{DD} =-V_{DET}-0.5 V	CJ808 C/N 20～26	3.0	13.0	—	mA
			CJ808 C/N 26～39	3.0	15.0	—	mA
			CJ808 C/N 39～60	3.0	18.0	—	mA
		PMOS: V_{DD}-V_{OUT} =0.5 V $V_{DD}=-V_{DET}+0.5V$	CJ808 C/N 20～26	1.5	4.0	—	mA
			CJ808 C/N 26～39	1.5	6.0	—	mA
			CJ808 C/N 39～60	1.5	8.0	—	mA
Leakage current	I_{LEAK}	Only for NMOS open-drain output products, V_{DD} =8.0 V, V_{OUT} =8.0 V			—	1.0	uA
temperature coefficient		Ta=−40°C ~+85°C		—	±120	±360	ppm/°C
Delay time	T_{PLH}				200		us


***1.** $-V_{DET}$: Actual detection voltage value, $-V_{DET(S)}$: Specified detection voltage value


■ TYPICAL APPLICATION CIRCUITS

1、CMOS output




2、NMOS open-drain








3. Forbidden Circuits



SOT-23 Package Outline Dimensions









Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP.		0.037 TYP.	
e1	1.800	2.000	0.071	0.079
L	0.550 REF.		0.022 REF.	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

SOT-23 Suggested Pad Layout




Note:
1.Controlling dimension:in millimeters.
2.General tolerance:±0.05mm.
3.The pad layout is for reference purposes only.

SOT-23-3L Package Outline Dimensions




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	2.650	2.950	0.104	0.116
E1	1.500	1.700	0.059	0.067
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°

SOT-23-3L Suggested Pad Layout




Note:
1.Controlling dimension:in millimeters.
2.General tolerance:± 0.05mm.
3.The pad layout is for reference purposes only.

SOT-23-5L Package Outline Dimensions




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	2.650	2.950	0.104	0.116
E1	1.500	1.700	0.059	0.067
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°

SOT-23-5L Suggested Pad Layout




Note:
1.Controlling dimension:in millimeters.
2.General tolerance:± 0.05mm.
3.The pad layout is for reference purposes only.

SOT-89-3L Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.400	1.600	0.055	0.063
b	0.320	0.520	0.013	0.197
b1	0.400	0.580	0.016	0.023
c	0.350	0.440	0.014	0.017
D	4.400	4.600	0.173	0.181
D1	1.550 REF		0.061 REF	
E	2.300	2.600	0.091	0.102
E1	3.940	4.250	0.155	0.167
e	1.500 TYP		0.060 TYP	
e1	3.000 TYP		0.118 TYP	
L	0.900	1.200	0.035	0.047

SOT-89-3L Suggested Pad Layout



Note:
1.Controlling dimension:in millimeters.
2.General tolerance:±0.05mm.
3.The pad layout is for reference purposes only.

DISCLAIMER

IMPORTANT NOTICE, PLEASE READ CAREFULLY

The information in this data sheet is intended to describe the operation and characteristics of our products. SZCJ has the right to make any modification, enhancement, improvement, correction or other changes to any content in this data sheet, including but not limited to specification parameters, circuit design and application information, without prior notice.

Any person who purchases or uses SZCJ products for design shall: 1. Select products suitable for circuit application and design; 2. Design, verify and test the rationality of circuit design; 3. Procedures to ensure that the design complies with relevant laws and regulations and the requirements of such laws and regulations. SZCJ makes no warranty or representation as to the accuracy or completeness of the information contained in this data sheet and assumes no responsibility for the application or use of any of the products described in this data sheet.

Without the written consent of SZCJ , this product shall not be used in occasions requiring high quality or high reliability, including but not limited to the following occasions: medical equipment, automotive electronics, military facilities and aerospace. SZCJ shall not be responsible for casualties or property losses caused by abnormal use or application of this product.

Official Website: www.szcjsemi.com

Copyright © SHENZHEN CHANGJI :LECTRONICS TECHNOLOGY CO., LTD.