
JIANGSU CHANGJING ELECTRONICS TECHNOLOGY CO., LTD.

SOT-23 Plastic-Encapsulate Transistors

A1015 TRANSI STOR (PNP)

SOT-23



1. BASE
2. EMITTER
3. COLLECTOR

FEATURES

- **High voltage and high current**
- **Excellent h_{FE} Linearity**
- **Complementary to C1815**

MARKING: BA

MAXIMUM RATINGS (T_a=25℃ unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	-50	V
V_{CEO}	Collector-Emitter Voltage	-50	V
V_{EBO}	Emitter-Base Voltage	-5	V
I_C	Collector Current -Continuous	-150	mA
P_C	Collector Power Dissipation	200	mW
$R_{\theta JA}$	Thermal Resistance From Junction To Ambient	625	℃/W
T_J,T_{stg}	Junction Temperature	-55~+150	℃


ELECTRICAL CHARACTERISTICS (T_a=25℃ unless otherwise specified)


Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	I_C= -100u A,I_E=0	-50			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	I_C= -0.1mA, I_B=0	-50			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	I_E= -100 u A, I_C=0	-5			V
Collector cut-off current	I_{CBO}	V_{CB}=-50V ,I_E=0			-0.1	μA
Collector cut-off current	I_{CEO}	V_{CE}= -50V , I_B=0			-1	μA
Emitter cut-off current	I_{EBO}	V_{EB}=- 5V, I_C=0			-0.1	μA
DC current gain	h_{FE}	V_{CE}=-6V,I_C= -2mA	120		400	
Collector-emitter saturation voltage	$V_{CE(sat)}$	I_C=-100 mA, I_B= -10mA			-0.3	V
Base-emitter saturation voltage	$V_{BE(sat)}$	I_C=-100 mA, I_B= -10mA			-1.1	V
Transition frequency	f_T	V_{CE}=-10V,I_C= -1mA f=30MHz	80			MHz


CLASSIFICATION OF h_{FE}


Rank	L	H
Range	120-240	200- 400


Typical Characteristics























SOT-23 Package Outline Dimensions








Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°


SOT-23 Suggested Pad Layout



Note:
1.Controlling dimension:in millimeters.
2.General tolerance:± 0.05mm.
3.The pad layout is for reference purposes only.

NOTICE
JSCJ reserves the right to make modifications,enhancements,improvements,corrections or other changes without further notice to any product herein. JSCJ does not assume any liability arising out of the application or use of any product described herein.

SOT-23 Embossed Carrier Tape




Packaging Description:


SOT-23 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-23	3.15	2.77	1.22	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

SOT-23 Tape Leader and Trailer



SOT-23 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	203×203×195	180,000 pcs	438×438×220	