SZCJ


Shenzhen Changji Semiconductor Co., LTD.

DFNWB2×2-6L Plastic-Encapsulate MOSFETS

CJM3005 N-Channel MOSFET

$V_{(BR)DSS}$	$R_{DS(on)}$TYP	I_D
30V	32mΩ@10V	5A
	35 mΩ@4.5V	
	42mΩ@2.5V	

DFNWB2×2-6L




FEATURE

- TrenchFET Power MOSFET
- Low $R_{DS(ON)}$
- Typical ESD Protection

APPLICATION

- Ideal for Load Swith and Battery Protection Applications

MARKING




3005 = Part No.

Solid dot = Pin1 indicator.

XX = Code.

Equivalent Circuit



ABSOLUTE MAXIMUM RATINGS (T_a=25℃ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	30	V
Gate-Source Voltage	V_{GS}	±10	V
Continuous Drain Current	I_D	5	A
Pulsed Drain Current	I_{DM}*	20	A
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	250	℃/W
Operation Junction and Storage Temperature Range	T_J,T_{STG}	-55~+150	℃

*Repetitive rating：Pluse width limited by junction temperature.

MOSFET ELECTRICAL CHARACTERISTICS

T_a=25℃ unless otherwise specified


Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
STATIC PARAMETERS						
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS} = 0V, I_D =250μA	30			V
Zero gate voltage drain current	I_{DSS}	V_{DS} =30V,V_{GS} = 0V			1	μA
Gate-body leakage current	I_{GSS}	V_{GS} =±10V, V_{DS} = 0V			±10	μA
Gate threshold voltage(note 1)	$V_{GS(th)}$	V_{DS} =V_{GS}, I_D =250μA	0.6		1	V
Drain-source on-resistance (note 1)	$R_{DS(on)}$	V_{GS} =10V, I_D =5A	22	32	42	mΩ
		V_{GS} =4.5V, I_D =5A	25	35	44	mΩ
		V_{GS} =2.5V, I_D =4A	32	42	50	mΩ
Forward tranconductance (note 1)	g_{FS}	V_{DS} =5V, I_D =4A		15		S
Diode forward voltage (note 1)	V_{SD}	I_S=1A, V_{GS} = 0V			1	V
DYNAMIC PARAMETERS (note2)						
Input Capacitance	C_{iss}	V_{DS} =15V,V_{GS} =0V,f =1MHz		245		pF
Output Capacitance	C_{oss}			35		pF
Reverse Transfer Capacitance	C_{rss}			20		pF
SWITCHING PARAMETERS (note 2)						
Turn-on delay time	$t_{d(on)}$	V_{DD}=15V,V_{GS}=10V R_L=3.75Ω,R_{GEN}=3Ω		2		ns
Turn-on rise time	t_r			3.5		ns
Turn-off delay time	$t_{d(off)}$			22		ns
Turn-off fall time	t_f			3.5		ns
Total Gate Charge	Q_g	V_{DS} =15V,V_{GS} =10V,I_D=4A			10	nC
Gate-Source Charge	Q_{gs}			0.5		nC
Gate-Drain Charge	Q_{gd}			1		nC

Notes : 1. Pulse Test : Pulse width≤300μs, duty cycle≤0.5%.


2. Guaranteed by design, not subject to production testing.

Typical Characteristics


Output Characteristics




Transfer Characteristics




$R_{DS(ON)}$ —— I_D




$R_{DS(ON)}$ —— V_{GS}




I_S —— V_{SD}




Threshold Voltage




DFNWB2X2-6L-J Package Outline Dimensions



TOP VIEW
[顶视图]




BOTTOM VIEW
[背视图]



SIDE VIEW
[侧视图]

Symbols	Dimensions in Milimeters		Dimensions in Inches	
	Min.	Max.	Min.	Max.
A	0.700	0.800	0.028	0.031
A1	0.000	0.050	0.000	0.002
A3	0.203REF.		0.008REF.	
D	1.900	2.100	0.075	0.083
E	1.900	2.100	0.075	0.083
D1	0.800	1.000	0.031	0.039
E1	0.850	1.050	0.033	0.041
D2	0.200	0.400	0.008	0.016
E2	0.460	0.660	0.018	0.026
b	0.250	0.350	0.010	0.014
e	0.650BSC.		0.026BSC.	
k	0.275REF.		0.011REF.	
k1	0.350REF.		0.014REF.	
L	0.174	0.326	0.007	0.013

DFNWB2X2-6L-J Suggested Pad Layout




Note:
1.Controlling dimension:in millimeters.
2.General tolerance:± 0.050mm.
3.The pad layout is for reference purposes only.

NOTICE

SZCJ reserves the right to make modifications,enhan nts,improvements,corrections or other es without further notice to any product herein. SZCJ does not assume any liability arising out of the application or use of any product described h

DFNWB2X2-6L Tape and Reel

DFNWB2×2-6L Embossed Carrier Tape




Packaging Description:


DFNWB2×2-6L parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 18.0cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	a	B	C	d	E	F	P0	P	P1	W
DFNWB2×2-6L	2.30	2.30	1.10	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

DFNWB2×2-6L Tape Leader and Trailer



DFNWB2×2-6L Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø180.00	60.00	13.00	R78.00	R25.60	R6.50	9.50	13.10

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	30,000 pcs	203×203×195	120,000 pcs	438×438×220	