
SZCJ Shenzhen Changji Semiconductor Co., LTD.

SOT-23 Plastic-Encapsulate MOSFETS

CJ3420 N-Channel Enhancement Mode Field Effect Transistor

$V_{(BR)DSS}$	$R_{DS(on)}$MAX	I_D
20V	24mΩ@10V	6A
	27mΩ@4.5V	
	42mΩ@2.5V	
	74mΩ@1.8V	

SOT-23




1. GATE
2. SOURCE
3. DRAIN

DESCRIPTION


The CJ3420 uses advanced trench technology to provide excellent $R_{DS(on)}$.This device is suitable for use as a uni-directional or bi-directional load switch.

MARKING



R20 = Device code
Solid dot = Green molding compound device.

Equivalent Circuit



Maximum ratings (T_a=25℃ unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	20	V
Gate-Source Voltage	V_{GS}	±12	
Continuous Drain Current	I_D	6	A
Pulsed Drain Current	I_{DM}	25	
Power Dissipation	P_D	0.35	W
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	357	℃/W
Operation Junction and Storage Temperature Range	T_J,T_{stg}	-55 ~+150	℃

MOSFET ELECTRICAL CHARACTERISTICS

T_a=25℃ unless otherwise specified

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-source breakdown voltage	$V_{(BR)\ DSS}$	V_{GS} = 0V, I_D =250μA	20			V
Zero gate voltage drain current	I_{DSS}	V_{DS} =16V,V_{GS} = 0V,T_J=25℃			1	μA
		V_{DS} =16V,V_{GS} = 0V,T_J=125℃			1	mA
Gate-source leakage current	I_{GSS}	V_{GS} =±12V, V_{DS} = 0V			±100	nA
On characteristics						
Drain-source on-resistance②	$R_{DS(on)}$	V_{GS} =10V, I_D =6A		19	24	mΩ
		V_{GS} =4.5V, I_D =5A		22	27	mΩ
		V_{GS} =2.5V, I_D =4A		27	42	mΩ
		V_{GS} =1.8V, I_D =2A		38	74	mΩ
Forward transconductance	g_{FS}	V_{DS} =5V, I_D =3.8A	4			S
Gate threshold voltage	$V_{GS(th)}$	V_{DS} =V_{GS}, I_D =250μA	0.5	0.7	1.0	V
Dynamic Characteristics③						
Input capacitance	C_{iss}	V_{DS} =10V,V_{GS} =0V,f =1MHz		630		pF
Output capacitance	C_{oss}			164		pF
Reverse transfer capacitance	C_{rss}			137		pF
Gate resistance	R_g	V_{DS} =0V,V_{GS} =0V,f =1MHz		1.5		Ω
Switching Characteristics③						
Turn-on delay time	$t_{d(on)}$	V_{GS}=10V,V_{DS}=15V, R_L=2.7Ω,R_{GEN}=3Ω		5.5		ns
Turn-on rise time	t_r			14		ns
Turn-off delay time	$t_{d(off)}$			29		ns
Turn-off fall time	t_f			10.2		ns
Total Gate Charge	Q_g	V_{DS}=10V,I_D=6A, V_{GS}=4.5V		8.8		nC
Gate-Source Charge	Q_{gs}			1		nC
Gate-Drain Charge	Q_{gd}			3.7		nC
Drain-source diode characteristics and maximum ratings						
Diode forward voltage②	V_{SD}	I_S=1A,V_{GS}=0V		0.75	1	V
Continuous drain-source diode forward current	I_S				6	A
Pulsed drain-source diode forward current①	I_{SM}				25	A

Notes:


1.Repetitive Rating : Pulse width limited by maximum junction temperature.

2.Pulse Test : Pulse Width≤300μs, Duty Cycle ≤ 2%.


3.Guaranteed by design, not subject to production testing.

Typical Characteristics


Output Characteristics




Transfer Characteristics




$R_{DS(ON)}$—— I_D




$R_{DS(ON)}$—— V_{GS}




I_S —— V_{SD}





Threshold Voltage



SOT-23 Package Outline Dimensions








Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP		0.037 TYP	
e1	1.800	2.000	0.071	0.079
L	0.550 REF		0.022 REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

SOT-23 Suggested Pad Layout




Note:
1.Controlling dimension:in millimeters.
2.General tolerance:± 0.05mm.
3.The pad layout is for reference purposes only.

NOTICE

SZCJ reserves the right to make modifications,enhan nts,improvements,corrections or other es without further notice to any product herein. SZCJ does not assume any liability arising out of the application or use of any product described h

SOT-23 Tape and Reel

SOT-23 Embossed Carrier Tape




Packaging Description:


SOT-23 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-23	3.15	2.77	1.22	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

SOT-23 Tape Leader and Trailer



SOT-23 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	203×203×195	180,000 pcs	438×438×220	