SZCJ

Shenzhen Changji Semiconductor Co., LTD.


TO-263-2L Plastic-Encapsulate Diode

SBDB20H100LCTB SCHOTTKY BARRIER RECTIFIER


MAIN CHARACTERISTICS

I_O	20（2×10）A
V_{RRM}	100 V
T_j	175 ℃
$V_{F(typ)}$	0.64V （@Tj=150℃）

TO-263-2L




1. ANODE
2. CATHODE
3. ANODE



FEATURES

- Low Power Loss,High Efficiency
- Guard Ring Die Construction for Transient Protection
- High Current Capability and Low Forward Voltage Drop

MARKING



SBDB20H100LCTB = Device code
Solid dot = Green molding compound device if none, the normal device

XXXX = Code

MAXIMUM RATINGS (T_a=25℃ unless otherwise noted)


Symbol	Parameter	Value	Unit
V_{RRM}	Peak repetitive reverse voltage	100	V
V_{RWM}	Working peak reverse voltage		
V_R	DC blocking voltage		
$V_{R(RMS)}$	RMS reverse voltage	71	V
I_O	Average rectified output current	20	A
I_{FSM}	Non-Repetitive peak forward surge current (8.3ms half sine wave)	300	A
$R_{\Theta Jc}$	Thermal resistance from junction to case ,Tc=25℃	2.0	℃/W
$R_{\Theta JA}$	Thermal resistance from junction to ambient	62.5	℃/W
T_j	Junction temperature	175	℃
T_{stg}	Storage temperature	-55~+175	℃

ELECTRICAL CHARACTERISTICS (T_a=25℃ unless otherwise specified)


Parameter	Symbol	Test conditions		Min	Typ	Max	Unit
Reverse voltage	$V_{(BR)}$	I_R=100uA		100			V
Reverse current	I_R	V_R=100V	Tj =25℃		0.2	0.5	uA
			Tj =150℃		2.0		mA
Forward voltage	V_F	I_F=5A	Tj =25℃		0.68		V
			Tj =150℃		0.51		V
		I_F=10A	Tj =25℃		0.74	0.80	V
			Tj =150℃		0.64		V

*Pulse test: pulse width ≤300μs, duty cycle≤ 2.0%.


Forward Characteristics




Reverse Characteristics




Capacitance Characteristics Per Diode



FORWARD CURRENT DERATING CURVE




TO-263-2L Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	4.470	4.670	0.176	0.184
A1	0.000	0.150	0.000	0.006
B	1.120	1.420	0.044	0.056
b	0.710	0.910	0.028	0.036
b1	1.170	1.370	0.046	0.054
c	0.310	0.530	0.012	0.021
c1	1.170	1.370	0.046	0.054
D	10.010	10.310	0.394	0.406
E	8.500	8.900	0.335	0.350
e	2.540 TYP.		0.100 TYP.	
e1	4.980	5.180	0.196	0.204
L	14.940	15.500	0.588	0.610
L1	4.950	5.450	0.195	0.215
L2	2.340	2.740	0.092	0.108
L3	1.300	1.700	0.051	0.067
Φ	0°	8°	0°	8°
V	5.600 REF.		0.220REF.	


TO-263-2L Suggested Pad Layout



Note:
1.Controlling dimension:in millimeters.
2.General tolerance:±0.05mm.
3.The pad layout is for reference purposes only.

TO-263-2L Tape and Reel

TO-263-2L Embossed Carrier Tabe




Packaging Description:


TO-263-2L parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Hear Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 800 units per 13″ or 33.0 cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
TO-263	10.80	16.13	5.21	Φ1.55	1.75	11.50	4.00	16.00	2.00	24.00

TO-263-2L Tape Leader and Trailer



TO-263-2L Reel



Dimensions are in millimeter						
Reel	D	D1	D2	W1	W2	I
13" Dia	330.00	100.00	Φ21.00	24.40	30.40	Φ13.00

Reel	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)
800 pcs	13 inch	1600 pcs	360×360×65	8000 pcs	378×358×382

szcjsemi.com