SZCJ


Shenzhen Changji Semiconductor Co., LTD.

JSCJ

PDFNWB5×6-8L Plastic-Encapsulate MOSFET

CJAC70N03S N-Channel Power MOSFET

$V_{(BR)DSS}$	$R_{DS(on)}$TYP	I_D
30 V	4.8mΩ@10V	70A
	6.5mΩ@4.5V	



DESCRIPTION

The CJAC70N03S uses advanced trench technology and design to provide excellent $R_{DS(ON)}$ with low gate charge. It can be used in a wide variety of applications.


FEATURES

- Battery switch
- Load switch
- High density cell design for ultra low $R_{DS(ON)}$
- Fully characterized avalanche voltage and current
- Excellent package for good heat dissipation

APPLICATIONS

- SMPS and general purpose applications
- Hard switched and high frequency circuits
- Uninterruptible Power Supply

MARK




CJAC70N03S = Part No.

Solid dot = Pin1 indicator

XX = Code

EQUIVALENT CIRCUIT



MAXIMUM RATINGS (T_J=25℃ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	30	V
Gate-Source Voltage	V_{GS}	±20	V
Continuous Drain Current	I_D ①	70	A
Pulsed Drain Current	I_{DM} ①②	280	A
Single Pulsed Avalanche Energy	E_{AS} ③	120	mJ
Power Dissipation	P_D ①	65	W
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$ ⑤	62.5	℃/W
Thermal Resistance from Junction to Case	$R_{\theta JC}$ ①	1.92	℃/W
Operating Junction and Storage Temperature Range	T_J ,T_{STG}	-55~+150	℃

MOSFET ELECTRICAL CHARACTERISTICS

T_J=25℃ unless otherwise specified

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Off characteristics							
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS} = 0V, I_D =10mA		30	-	-	V
Zero gate voltage drain current	I_{DSS}	V_{DS} =24V, V_{GS} =0V	T_J =25℃	-	-	1.0	μA
			T_J =125℃	-	-	100	
Gate-body leakage current	I_{GSS}	V_{DS} =0V, V_{GS} =±20V		-	-	±100	nA
On characteristics ④							
Gate-threshold voltage	$V_{GS(th)}$	V_{DS} =V_{GS}, I_D =250μA		1.0	1.5	2.5	V
Static drain-source on-sate resistance	$R_{DS(on)}$	V_{GS} =10V, I_D =20A		-	4.8	6.0	mΩ
		V_{GS} =4.5V, I_D =20A		-	6.5	9.5	mΩ
Dynamic characteristics							
Input capacitance	C_{iss}	V_{DS} =15V,V_{GS} =0V, f =1MHz		-	2180	-	pF
Output capacitance	C_{oss}			-	282	-	
Reverse transfer capacitance	C_{rss}			-	213	-	
Gate resistance	R_g	f =1MHz		-	4.0	-	Ω
Switching characteristics							
Total gate charge	Q_g	V_{GS}=4.5V, V_{DS}=15V, I_D=20A		-	20	-	nC
Total gate charge	Q_g	V_{GS}=10V, V_{DS}=15V, I_D=20A		-	41	-	
Gate-source charge	Q_{gs}			-	4.9	-	
Gate-drain charge	Q_{gd}			-	7.2	-	
Turn-on delay time	$t_{d(on)}$	V_{DS}=15V, VGS=10V, R_L=1.2Ω , R_g=10Ω		-	30	-	ns
Turn-on rise time	t_r			-	35	-	
Turn-off delay time	$t_{d(off)}$			-	60	-	
Turn-off fall time	t_f			-	36	-	
Drain-Source Diode Characteristics							
Drain-source diode forward voltage	V_{SD} ④	V_{GS} =0V, I_S=20A		-	-	1.2	V
Continuous drain-source diode forward current	I_S ①			-	-	70	A
Pulsed drain-source diode forward current	I_{SM} ①②			-	-	280	A

Notes:

1.T_C=25°℃.

2.Limited only by maximum temperature allowed.

3.V_{DD}=15V,V_{GS}=10V, L=0.5mH, Rg=25Ω Starting T_J= 25°℃.


4.Pulse Test : Pulse Width≤380μs, duty cycle ≤2%.

5.Device mounted on 1 in² FR-4 board with 2oz. single-sided Copper, in a still air environment with T_A=25 ℃.


szqsemi.com

Typical Characteristics (T_J = 25℃, unless otherwise specified)


Output Characteristics




Transfer Characteristics




On Resistance vs. Drain Current




On Resistance vs. Gate-Source Bias



On Resistance vs. Junction Temperature




Gate-Source Threshold Voltage




szcjsemi.com

Typical Characteristics (T_J = 25℃, unless otherwise specified)


Typical Capacitances




Gate Charge




Source-Drain Diode Forward Characteristics



Maximum Safe Operating Area




Transient Thermal Impedance, Junction-Case




szcjsemi.com


TEST CIRCUIT AND WAVEFOMRS


Gate Charge






Resistive Load Switching Time






Un-clamped Inductive Load Switching




$E_{AS} = 1/2 \times L \times I_{AS}^2$




szqsemi.com


PDFNWB5×6-8L PACKAGE OUTLINE DIMENSIONS



Top View
[顶视图]



Bottom View
[背视图]




Side View
[侧视图]

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.90	1.10	0.035	0.043
A1	0.25 REF.		0.010 REF.	
D4.90		5.10	0.193 0.201	
D14.80		5.00	0.189 0.197	
D23.90		4.10	0.154 0.161	
E	5.90	6.10	0.232	0.240
E15.65		5.85	0.222 0.230	
E23.35		3.65	0.132 0.144	
k1.20		1.50	0.047 0.059	
b0.20		0.45	0.008 0.018	
e	1.27 BSC		0.050 BSC	
L0.55		0.75	0.022 0.030	
H0.45		0.75	0.018 0.030	

Notes：
1 Dimensions exclusive of mold gate burrs.
2 Dimensions exclusive of mold flash and cutting burrs.

PDFNWB5×6-8L Suggested Pad Layout



Notes：
1 Controlling dimension：in millimeters.
2 General tolerance:±0.05mm.
3 The pad layout is for referance purpose only.


NOTICE

SZCJ reservesthe right to make modifications,enhancements,improvements,corrections or other changes without further notice to any product herein.SZCJ does not assume any liability arising out of the application or use of any product described herein.

szcjsemi.com

PDFNWB5×6-8L Tape and Reel

PDFNWB5×6-8L Embossed Carrier Tape




Packaging Description:


PDFNWB5×6-8L parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 5,000 units per 13" or 33.0 cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
PDFNWB5×6-8L	6.30	5.30	1.10	Ø1.50	1.75	5.50	4.00	8.00	2.00	12.00

PDFNWB5×6-8L Tape Leader and Trailer



PDFNWB5×6-8L Reel



Dimensions are in millimeter						
Reel Option	**D**	**D1**	**D2**	**G**	**W1**	**W2**
13" Dia	φ330.00	100.00	13.00	1.90	17.60	12.40

Reel	Reel Size	Box	Box Size (mm)	Carton	Carton Size (mm)
5,000 pcs	13 inch	10,000 pcs	360×360×65	50,000 pcs	378×358×382

szcsemi.com