SZCJ


Shenzhen Changji Semiconductor Co., LTD.

SOT-323 Plastic-Encapsulate Diodes

BAT54LW/ALW/CLW/SLW

SCHOTTKY BARRIER DIODE

SOT-323



FEATURES

- Extremely Fast Switching Speed
- Low forward voltage



BAT54LW BAT54ALW BAT54CLW BAT54SLW

MARKING:

BAT54LW	BAT54ALW	BAT54CLW	BAT54SLW
KL5L	KL6L	KL7L	KL8L

Solid dot = Green molding compound device.

MAXIMUM RATINGS (T_a=25℃ unless otherwise noted)


Parameter	Symbol	Value	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	30	V
Forward Continuous Current	I_{FM}	200	mA
Non-repetitive Peak Forward Surge Current @ t=8.3ms	I_{FSM}	600	mA
Repetitive Peak Forward Current @ t≤1s, δ ≤0.5	I_{FRM}	300	mA
Power Dissipation	P_D	200	mW
Thermal Resistance from Junction to Ambient	$R_{\Theta JA}$	500	℃/W
Operating Junction Temperature Range	T_j	-40 ~ +125	℃
Storage Temperature Range	T_{stg}	-55 ~ +150	℃

ELECTRICAL CHARACTERISTICS(T_a=25℃ unless otherwise specified)


Parameter	Symbol	Min	Typ	Max	Unit	Test conditions
Reverse voltage	$V_{(BR)}$	30			V	I_R=100μA
Forward voltage	V_F		0.23	0.27	V	I_{F1}=0.1mA
			0.29	0.32	V	I_{F2}=1mA
			0.37	0.40	V	I_{F3}=10mA
			0.42	0.50	V	I_{F4}=30mA
			0.55	1	V	I_{F5}=100mA
Reverse current	I_R		0.085	2	μA	V_R=25V
Diode capacitance	C_D			12	pF	V_R=1V,f=1MHz
Reverse recovery time	t_{rr}			5	ns	I_F=I_R=10mA Irr=0.1×I_R,R_L=100Ω

Typical Characteristics


Forward Characteristics




Reverse Characteristics




Capacitance Characteristics





Power Derating Curve



SOT-323 Package Outline Dimensions








Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.200	0.400	0.008	0.016
c	0.080	0.150	0.003	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.450	0.085	0.096
e	0.650 TYP		0.026 TYP	
e1	1.200	1.400	0.047	0.055
L	0.525 REF		0.021 REF	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°

SOT-323 Suggested Pad Layout




Note:
1.Controlling dimension:in millimeters.
2.General tolerance:±0.05mm.
3.The pad layout is for reference purposes only.

NOTICE

SZCJ reserves the right to make modifications,enhan nts,improvements,corrections or other es without further notice to any product herein. SZCJ does not assume any liability arising out of the application or use of any product described h

SOT-323 Tape and Reel

SOT-323 Embossed Carrier Tape




Packaging Description:


SOT-323 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-323	2.25	2.55	1.19	Ø1.55	1.75	3.50	4.00	4.00	2.00	8.00

SOT-323 Tape Leader and Trailer



SOT-323 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	203×203×195	180,000 pcs	438×438×220	