JIANGSU CHANGJING ELECTRONICS TECHNOLOGY CO., LTD.

TO-251 Plastic-Encapsulate Transistors


B772M TRANSISTOR （PNP)

FEATURES


● Low Speed Switching

TO-251

1. EMITTER
2. COLLECTOR
3. BASE




MARKING



B722=Device code
Solid dot=Green moldinn compound device, if none,the normal device
XXXX=Code

Equivalent Circuit



MAXIMUM RATINGS (T_a=25℃ unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	-40	V
V_{CEO}	Collector-Emitter Voltage	-30	V
V_{EBO}	Emitter-Base Voltage	-6	V
I_C	Collector Current -Continuous	-3	A
P_C	Collector Power Dissipation	1.25	W
$R_{\Theta JA}$	Thermal Resistance, junction to Ambient	100	℃/W
T_J,T_{stg}	Operation Junction and Storage Temperature Range	-55-150	℃


ELECTRICAL CHARACTERISTICS (T_a=25℃ unless otherwise specified)


Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	I_C=-100μA ,I_E=0	-40			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	I_C= -10mA , I_B=0	-30			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	I_E= -100μA,I_C=0	-6			V
Collector cut-off current	I_{CBO}	V_{CB}= -40V, I_E=0			-1	μA
Collector cut-off current	I_{CEO}	V_{CE}=-30V, I_B=0			-10	μA
Emitter cut-off current	I_{EBO}	V_{EB}=-6V, I_C=0			-1	μA
DC current gain	h_{FE}	V_{CE}= -2V, I_C= -1A	60		400	
Collector-emitter saturation voltage	$V_{CE(sat)}$	I_C=-2A, I_B= -0.2A			-0.5	V
Base-emitter saturation voltage	$V_{BE(sat)}$	I_C=-2A, I_B= -0.2A			-1.5	V
Transition frequency	f_T	V_{CE}= -5V, I_C=-0.1A f =10MHz	50	80		MHz


CLASSIFICATION OF h_{FE}


Rank	R	O	Y	GR
Range	60-120	100-200	160-320	200-400


Typical Characteristics


















TO-251 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.200	2.400	0.087	0.094
A1	1.050	1.350	0.042	0.054
B	1.350	1.650	0.053	0.065
b	0.500	0.700	0.020	0.028
b1	0.700	0.900	0.028	0.035
c	0.430	0.580	0.017	0.023
c1	0.430	0.580	0.017	0.023
D	6.350	6.650	0.250	0.262
D1	5.200	5.400	0.205	0.213
E	5.400	5.700	0.213	0.224
e	2.300 TYP.		0.091 TYP.	
e1	4.500	4.700	0.177	0.185
L	7.500	7.900	0.295	0.311